



Water Dispenser

Professional water dispenser manufacturer



Ningbo Feter Electrical Appliance Co., Ltd

Add: 78 Jingqi Road, Fuhai Industrial Zone, Cixi City, Zhejiang Province

Tel: 86-574-63564720 Fax: 86-574-63567353

Mail: feter@feterchina.com

Web: www.feterchina.com

QUALIFICATIONS AND HONORS



CERTIFICATIONS ----- 01-02

COMPANY PROFILE ----- 03-04

WATER DISPENSER WITH ICE MAKER ----- 05-06

BOTTOM LOADING WATER DISPENSER ----- 07-10

TOP LOADING WATER DISPENSER ----- 11-29



COMPANY PROFILE

Ningbo Feter Electrical Appliance Co., Ltd—founded in 2003 focus on cooling industry for 23 years.

Ningbo Feter Electrical Appliance Co., Ltd was founded in 2003, is a professional manufacturer and exporter of Water Dispenser and other appliances.

Factory has over 30,000 square meters and 200 employees, annual sales exceed 15 million dollars and export to more than 150 countries and regions around the world. Our partners include Wal-Mart, LIDL and other international companies.

We are a company who combines design, mold development, mold injection, assembling and owns professional R&D department with more than 20 people to provide OEM, ODM service for customers.

Company is a verified supplier of Alibaba and Made-in-China, which passed ISO9001 International Quality System and BSCI inspection by SGS and BV.

Our products have been awarded over 200 patents and complied with international quality standards such as ETL, CE, GS, CB, PSE, FCC and other certifications.

Ningbo Feter Electrical Appliance Co., Ltd is always looking forward to sincere cooperation relationship with all of customers!



23+ YEARS

Founded in 2003

3000m2

Factory Area

200+

Employees

OEM & ODM

R&D Team



Our Advantage

- ◆ High-efficiency compressor improve cooling capability and increase life span of 20%
- ◆ High-strength metal panel improve stability and increasing the bearing capacity of 15%
- ◆ Food-grade stainless steel tank,more clean,sanitary and safe
- ◆ Food-grade imported high polymer material for plastic parts.No odor,more luster and durable
- ◆ Creative refrigeration cycle and built-in refrigerator system is more efficient and energy-saving
- ◆ Elegant and user-friendly design match with popular trend



FETER

WATER DISPENSER WITH ICE MAKER



Hot Water



Cold water



Normal water



12Pcs



15KG/Day



Bullet ice



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-3120B	2L/H, 5-10°C	5L/H, 85-95°C	37x37x112cm	180PCS/20'GP; 384PCS/40HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-3150B	2L/H, 5-10°C	5L/H, 85-95°C	37x37x112cm	180PCS/20'GP; 384PCS/40HC

BOTTOM LOADING WATER DISPENSER



Diameter ≤ 28cm



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-XZS-317LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	37x35.5x108cm	455PCS/40HC
HSM-XZS-317LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x108cm	455PCS/40HC



Diameter ≤ 28cm



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-XZS-319LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	37x35.5x108cm	455PCS/40HC
HSM-XZS-319LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x108cm	455PCS/40HC



Product Parameter	
Model:	HSM-XZS-1906LA semiconductor cooling 1906LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	43.5x32.5x115.5cm
Loading Qty:	425PCS/40' HC

Product Parameter	
Model:	HSM-XZS-1909LA semiconductor cooling 1909LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	43.5x32.5x115.5cm
Loading Qty:	425PCS/40' HC

Product Parameter	
Model:	HSM-XZS-1910LA semiconductor cooling 1910LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	43.5x32.5x115.5cm
Loading Qty:	425PCS/40' HC

Product Parameter	
Model:	HSM-XZS-168LA semiconductor cooling 168LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	39.5x37.5x108.5cm
Loading Qty:	422PCS/40HC

Product Parameter	
Model:	HSM-XZS-318LA semiconductor cooling 318LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	37x35.5x108cm
Loading Qty:	455PCS/40HC

Product Parameter	
Model:	HSM-XZS-218LA semiconductor cooling 218LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	37x35.5x108cm
Loading Qty:	455PCS/40HC



Product Parameter	
Model:	HSM-XZS-1908LA semiconductor cooling 1908LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	43.5x32.5x115.5cm
Loading Qty:	425PCS/40' HC

Product Parameter	
Model:	HSM-XZS-1708LA semiconductor cooling 1708LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	43.5x32.5x115.5cm
Loading Qty:	425PCS/40' HC

Product Parameter	
Model:	HSM-XZS-1706LA semiconductor cooling 1706LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	43.5x32.5x115.5cm
Loading Qty:	425PCS/40' HC

Product Parameter	
Model:	HSM-XZS-1506LB compressor cooling
Cooling Capacity:	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	39.5x37.5x108.5cm
Loading Qty:	422PCS/40HC

Product Parameter	
Model:	HSM-XZS-118LB compressor cooling
Cooling Capacity:	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	39.5x37.5x108.5cm
Loading Qty:	422PCS/40HC

Product Parameter	
Model:	HSM-XZS-117LB compressor cooling
Cooling Capacity:	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	39.5x37.5x108.5cm
Loading Qty:	422PCS/40HC

DESKTOP WATER DISPENSER




TOP LOADING WATER DISPENSER





Product Parameter		
Model:	HSM-1910TA semiconductor cooling	1910TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	43.5x32.5x52cm	45.5x32.5x52cm
Loading Qty:	360PCS/20'GP 945PCS/40'HC	335PCS/20'GP 910PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1910LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1910LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1910LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-RO-1910LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC




Product Parameter		
Model:	HSM-1908TA semiconductor cooling	1908TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	43.5x32.5x52cm	45.5x32.5x52cm
Loading Qty:	360PCS/20'GP 945PCS/40'HC	335PCS/20'GP 910PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1908LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1908LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1908LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-RO-1908LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC



Product Parameter		
Model:	HSM-1909TA semiconductor cooling	1909TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	43.5x32.5x52cm	45.5x32.5x52cm
Loading Qty:	360PCS/20'GP 945PCS/40'HC	335PCS/20'GP 910PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1909LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1909LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1909LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-RO-1909LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC



Product Parameter		
Model:	HSM-1906TA semiconductor cooling	1906TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	43.5x32.5x52cm	45.5x32.5x52cm
Loading Qty:	360PCS/20'GP 945PCS/40'HC	335PCS/20'GP 910PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1906LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1906LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-1906LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC
HSM-RO-1906LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP;425PCS/40'HC



Product Parameter		
Model:	HSM-1708TA semiconductor cooling	1708TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	43.5x32.5x52cm	45.5x32.5x52cm
Loading Qty:	360PCS/20'GP 945PCS/40'HC	335PCS/20'GP 910PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1708LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC
HSM-1708LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC
HSM-1708LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC
HSM-RO-1708LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC

Product Parameter		
Model:	HSM-316TA semiconductor cooling	316TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-316LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-316LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-316LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-316LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-1706TA semiconductor cooling	1706TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	43.5x32.5x52cm	45.5x32.5x52cm
Loading Qty:	360PCS/20'GP 945PCS/40'HC	335PCS/20'GP 910PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1706LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC
HSM-1706LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC
HSM-1706LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC
HSM-RO-1706LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	43.5x32.5x115.5cm	182PCS/20'GP; 425PCS/40'HC

Product Parameter		
Model:	HSM-315TA semiconductor cooling	315TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	35x33x52cm	37x33x52cm
Loading Qty:	480PCS/20'GP 1150PCS/40'HC	420PCS/20'GP 1085PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-315LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-315LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-315LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-RO-315LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC



Product Parameter		
Model:	HSM-313TA semiconductor cooling	313TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	35x33x52cm	37x33x52cm
Loading Qty:	480PCS/20'GP 1150PCS/40'HC	420PCS/20'GP 1085PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-313LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-313LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-313LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-RO-313LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC



Product Parameter		
Model:	HSM-217TA semiconductor cooling	217TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	35x33x52cm	37x33x52cm
Loading Qty:	480PCS/20'GP 1150PCS/40'HC	420PCS/20'GP 1085PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-217LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-217LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-217LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC
HSM-RO-217LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	35x33x98cm	262PCS/20'GP; 600PCS/40'HC



Product Parameter		
Model:	HSM-310TA semiconductor cooling	310TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-310LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-310LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-310LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-310LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-92TA semiconductor cooling	92TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-92LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-92LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-92LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-92LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC





Product Parameter		
Model:	HSM-212TA semiconductor cooling	212TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-212LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-212LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-212LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-212LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC

Product Parameter		
Model:	HSM-98TA semiconductor cooling	98TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-98LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-98LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-98LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-98LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-211TA semiconductor cooling	211TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-211LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-211LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-211LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-211LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC

Product Parameter		
Model:	HSM-96TA semiconductor cooling	96TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-96LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-96LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-96LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-96LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-95TA semiconductor cooling	95TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-95LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-95LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-95LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-95LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-93TA semiconductor cooling	93TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-93LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-93LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-93LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-93LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-94TA semiconductor cooling	94TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-94LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-94LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-94LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-90TA semiconductor cooling	90TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-90LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-90LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-90LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-89TA semiconductor cooling	89TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-89LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-89LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-89LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-89LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC

Product Parameter		
Model:	HSM-65TA semiconductor cooling	65TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-65LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-65LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-65LBA compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-88TA semiconductor cooling	88TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-88LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-88LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-88LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-88LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC

Product Parameter		
Model:	HSM-64TA semiconductor cooling	64TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-64LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-64LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-64LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-64LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC



Product Parameter		
Model:	HSM-61TA semiconductor cooling	61TB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C	
Carton Size:	34x33x52cm	36x33x52cm
Loading Qty:	505PCS/20'GP 1180PCS/40'HC	448PCS/20'GP 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-61LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-61LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-61LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-RO-61LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-318LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC
HSM-318LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC
HSM-318LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC
HSM-RO-318LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC



Product Parameter	
Model:	HSM-16TB compressor cooling
Cooling Capacity:	2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95°C
Carton Size:	36x33x52cm
Loading Qty:	448PCS/20'GP; 1110PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-16LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-16LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC
HSM-16LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	34x33x98cm	270PCS/20'GP; 620PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-218LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC
HSM-218LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC
HSM-218LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC
HSM-RO-218LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	37x35.5x106cm	190PCS/20'GP; 455PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-168LA semiconductor cooling	0.75L/H, 10-15°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-168LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-168LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-RO-168LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-118LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-118LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-RO-118LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC



Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-1506LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-1506LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-RO-1506LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC

Model	Cooling Capacity	Heating Capacity	Carton Size	Loading Qty
HSM-117LB compressor cooling	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-117LBA with refrigerator	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC
HSM-RO-117LB compressor cooling with filters	2L/H, 5-10°C	5L/H, 85-95°C	39.5x37.5x108.5cm	168PCS/20'GP; 422PCS/40'HC



Product Parameter	
Model:	HSM-40LA semiconductor cooling 40LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95 °C
Carton Size:	32.5x29x86cm
Loading Qty:	365PCS/20'GP; 815PCS/40'HC



Product Parameter	
Model:	HSM-30LA semiconductor cooling 30LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95 °C
Carton Size:	32.5x29x86cm
Loading Qty:	365PCS/20'GP; 815PCS/40'HC



Product Parameter	
Model:	HSM-20LA semiconductor cooling 20LB compressor cooling
Cooling Capacity:	0.75L/H, 10-15°C 2L/H, 5-10°C
Heating Capacity:	5L/H, 85-95 °C
Carton Size:	31.5x29x86cm
Loading Qty:	365PCS/20'GP; 835PCS/40'HC



Product Parameter	
Model:	HSM-22TA semiconductor cooling
Cooling Capacity:	0.75L/H, 10-15°C
Heating Capacity:	5L/H, 85-95 °C
Carton Size:	30x30x38.5cm
Loading Qty:	910PCS/20'GP; 2000PCS/40'HC



Product Parameter	
Model:	HSM-21TA semiconductor cooling
Cooling Capacity:	0.75L/H, 10-15°C
Heating Capacity:	5L/H, 85-95 °C
Carton Size:	30x30x38.5cm
Loading Qty:	910PCS/20'GP; 2000PCS/40'HC



Product Parameter	
Model:	HSM-10TA semiconductor cooling
Cooling Capacity:	0.75L/H, 10-15°C
Heating Capacity:	5L/H, 85-95 °C
Carton Size:	32.5x32.5x42.5cm
Loading Qty:	690PCS/20'GP; 1500PCS/40'HC

SPARE PARTS

